

PlumbQwik by Fernco

- Provides a reliable flexible seal
- Designed for waste and grey water applications
- Connect what would normally be incompatible pipe systems
- Large range of straight and adaptor variations
- Quick and easy to install by tightening to 6Nm using a nut driver and a torque wrench
- Manufactured without the addition of phthalate plasticizers
- Remove and re-fit as required



PlumbQwik™ is a range of plumbing couplings by Fernco for above ground drainage applications, commonly found under kitchen sinks, shower trays, baths, behind washing machines etc.

Unlike many other plumbing couplings on the market, PlumbQwik's can connect any material pipe, provided it fits within the products size range. Made from flexible phthalate free PVC, the couplings can also adapt to imperfect

pipe alignment, making them ideal for repair scenarios and rectifying previous bad workmanship. The product range covers all common pipe sizes as straight or adaptor (also known as reducer) applications.



Straight PlumbQwik™



Adaptor PlumbQwik™



Elbow PlumbQwik™



Tee PlumbQwik™



End Cap PlumbQwik™

Fit horizontally or vertically

Strong stainless steel
clamp bands

High quality PVC
coupling body



Product Code	PQXXX
Description	PlumbQwik Coupling
Size Range	21-364mm
Material	Phthalate free PVC 1.4301 (304) Stainless Steel <i>Couplings with a different material makeup of 1.4404 Stainless Steel are available on request.</i>
Temperature Range	-34°C to 40°C constant, 60°C intermittent
Pressure Rating	0.5bar, 7.25psi



Straight PlumbQwik™ Range

Product Code	Size Range (mm)	Tightening Torque
PQ028	21-29	6Nm
PQ038	30-39	6Nm
PQ042	31-40	6Nm
PQ045	37-45	6Nm
PQ050	40-49	6Nm
PQ058	50-59	6Nm
PQ063	53-62	6Nm
PQ068	60-69	6Nm
PQ085	75-86	6Nm
PQ090	78-89	6Nm
PQ095	85-96	6Nm
PQ101	95-101	6Nm
PQ112	101-112	6Nm
PQ122	110-123	6Nm
PQ133	127-133	6Nm
PQ142	136-142	6Nm
PQ162	152-162	6Nm
PQ188	180-188	6Nm



Adaptor PlumbQwik™ Range

Product Code	Size Range A (mm)	Size Range B (mm)	Tightening Torque
PQ040-032	32-41	25-33	6Nm
PQ050-042	40-49	32-41	6Nm
PQ058-038	50-59	30-39	6Nm
PQ058-045	50-59	37-46	6Nm
PQ070-060	65-70	57-60	6Nm
PQ085-058	75-86	50-59	6Nm
PQ086-047	80-86	44-47	6Nm
PQ101-089	95-101	85-89	6Nm
PQ112-045	100-113	37-46	6Nm
PQ112-050	98-111	40-49	6Nm
PQ112-085	100-113	75-86	6Nm
PQ113-059	106-113	53-59	6Nm
PQ122-112	110-123	100-113	6Nm
PQ124-118	114-124	104-118	6Nm
PQ127-115	118-127	104-115	6Nm
PQ133-084	111-133	79-84	6Nm
PQ135-115	113-135	107-115	6Nm
PQ142-111	136-142	101-111	6Nm
PQ160-133	149-160	111-133	6Nm
PQ163-111	155-163	101-111	6Nm
PQ187-111	177-187	101-111	6Nm
PQ190-162	177-190	152-162	6Nm



Elbow PlumbQwik™ Range

Product Code	Size Range (mm)	Tightening Torque
PQE048	41-48	6Nm
PQE062	54-62	6Nm
PQE085	80-89	6Nm
PQE112	105-116	6Nm





Tee PlumbQwik™ Range

Product Code	Size Range (mm)	Tightening Torque
PQT048	41-48	6Nm
PQT062	54-62	6Nm
PQT085	80-89	6Nm
PQT112	105-116	6Nm



End Cap PlumbQwik™ Range

Product Code	Size Range (mm)	Tightening Torque
PQC028	25-28	6Nm
PQC042	35-47	6Nm
PQC048	43-50	6Nm
PQC060	54-63	6Nm
PQC070	60-70	6Nm
PQC089	80-89	6Nm
PQC100	88-100	6Nm
PQC112	108-114	6Nm
PQC125	115-125	6Nm
PQC142	135-146	6Nm
PQC162	150-162	6Nm
PQC181	170-181	6Nm
PQC215	204-220	6Nm
PQC230	233-237	6Nm
PQC250	243-257	6Nm
PQC274	268-280	6Nm
PQC328	322-334	6Nm
PQC358	352-364	6Nm

Installation



1. Mark both pipes from the end to be connected, half the width of the coupling.



2. Slide the coupling fully over one of the pipes.



3. Align the pipes and slide the coupling onto the other pipe, ensuring the coupling face and marked line are flush. Tighten this clamp band.



4. Position the remaining pipe, ensuring the coupling face and marked line are flush. Tighten this clamp band.



5. Tighten the clamp bands to 6Nm.

Note: The above instructions outline the method of connecting two pipes of the same diameter using a Straight PlumbQwik. This method can also be followed to make connections using other couplings in the PlumbQwik range.

General Information

Quality, Standards and Approvals

Fernco has been certified by the British Standards Institution (BSI) as a company of assessed capability, with a quality management system which meets the requirements of BS EN ISO 9001:2015

Fernco UK, part of a global group of companies, are the leaders in wastewater connection innovation; utilising the most advanced methods and techniques for precision-manufactured products, all of which comply with or exceed relevant British and European standards to ensure reliability and sustainability.

Environment

Fernco operate Environmental Management Systems which are certified to ISO 14001: 2015.

Supply

Fernco are proud members of the Builders Merchants Federation (BMF). All Fernco products are supplied through a national and global network of distribution and merchant partners. For stockist details, contact Fernco.

Technical Support

Fernco have a team of product experts on hand to support all customers with technical support and advice.

Contact Fernco Technical Department:

Tel: +44 (0) 1226 344100

Email: technical@fernco.co.uk

Enquiries

UK Sales:

Tel: +44 (0) 1226 340 888

Email: sales@fernco.co.uk

International Sales:

Tel: +44 (0) 1226 344 105

Email: export.dept@fernco.co.uk